

## NX-700/800

### NEXEDGE®

NEXEDGE® VHF/UHF Digital & Analog Mobile Radios

**NXDN®** FleetSync®

#### ● GENERAL FEATURES

- 30 W (136-174 MHz) Models
- 30 W (400-470 MHz) Models
- 512 CH-GID / 128 Zones
- Dash & Remote Mount
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- Function/Status LCD Icons
- Multi-Language Display
- Date & 12/24 Hour Time Clock
- Transmit/Busy/Call Alert/Warn LED
- On/Off Power Control
- 4 Up/Down Selectors
- 6 Front PF Keys
- Emergency/AUX Key
- 4W Speaker Audio
- DB-25 Accessory Connector
- 9 Programmable AUX I/Os
- 2 Programmable AUX Outputs
- KPG-111D Windows® FPU
- Flash Firmware Upgrading
- MIL-STD-810 C/D/E/F/G
- IP-54/55 Water & Dust Intrusion
- PC Serial Interface
- SDM Manual Input<sup>1</sup>
- Transparent Data Mode<sup>1</sup>
- GPS Receiver Option
- VGS-1 Voice Guide / Voice & GPS Data Storage Option

#### ● DIGITAL – COMMON

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Over-the-Air Programming
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging<sup>1</sup>
- Remote Stun/Kill<sup>1</sup>
- Remote Check<sup>1</sup>
- Short & Long Data Messages<sup>1</sup>
- GPS Location with Voice<sup>1</sup>
- NXDN® Scrambler Included

#### ● DIGITAL CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- Individual & Group Selective Call
- Mixed FM/Digital Operation
- Conventional IP Networks
- Site Roaming

#### ● DIGITAL TRUNKING MODE

- Individual Private Call
- Group Call & Broadcast Call
- Transmission Trunked Mode<sup>2</sup>
- Message Trunked Mode<sup>2</sup>
- Call Queuing with Priority<sup>2</sup>
- Late Entry (UID & GID)<sup>2</sup>
- 4 Priority Monitor ID's<sup>2</sup>
- Remote Group Add<sup>1</sup>
- Failsoft Mode

#### ● MULTI-SITE IP NETWORKS COMPATIBLE

- Individual Private Call
- Group Call & Broadcast Call
- Transmission Trunked Mode<sup>2</sup>

#### ● SCAN

- Single Zone / Multi-Zone / List Scan
- Dual Priority Scan (Conventional)



## Options

<ul style="list-style-type: none"> <li><b>KMC-35</b> Microphone</li> <li><b>KMC-36</b> Microphone with Keypad</li> <li><b>KMC-9C</b> Control Station Desktop Microphone</li> <li><b>KES-5</b> External Speaker</li> </ul>	<ul style="list-style-type: none"> <li><b>VGS-1</b> Voice Guide &amp; Storage Unit</li> <li><b>KRK-10</b> Panel Remote Kit</li> <li><b>KPS-15</b> DC Power Supply</li> </ul>	<ul style="list-style-type: none"> <li><b>KAP-2</b> Horn Alert / PA Relay Unit</li> <li><b>KCT-23M</b> DC Cable (10 feet)</li> <li><b>KCT-23M3</b> DC Cable (23 feet)</li> </ul>	<ul style="list-style-type: none"> <li><b>KCT-46</b> Ignition Sense Cable</li> <li><b>KMB-10</b> Key Lock Adapter</li> <li><b>KLF-2</b> Line Noise Filter</li> </ul>
---	--	--	--

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

## Main Specifications

		NX-700(H) K	NX-800(H) K
<b>GENERAL</b>			
<b>Frequency Range</b>	Type 1	136-174 MHz	
	Type 2		400-470 MHz
<b>Number of Channels</b>			512
<b>Zones</b>			128
<b>Max. Channels per Zone</b>			250
<b>Channel Spacing</b>	<b>Analog</b>	12.5 / 15 / 25 / 30 kHz	12.5 / 25 kHz
	<b>Digital</b>	6.25 / 12.5 kHz	6.25 / 12.5 kHz
<b>Operating Voltage</b>		13.6 V DC $\pm$ 15%	
<b>Operating Temperature Range</b>		-22° F to +140° F (-30° C to +60° C)	
<b>Frequency Stability</b>		$\pm$ 1.0 ppm	
<b>Antenna Impedance</b>		50 $\Omega$	
<b>Dimensions (W x H x D)</b>	Projections not included	6.30 x 1.77 x 6.18 in (160 x 45 x 157 mm)	
<b>Weight (net)</b>		3.04 lb (1.38 kg)	
<b>IC Certification</b>	<b>K</b> Type 1	282F-378600	
	<b>K</b> Type 2		282F-378701

Analog measurements made per TIA/EIA 603 and specifications shown are typical. Kenwood reserves the right to change specifications without prior notice or obligation.

FleetSync® is a registered trademark of JVC KENWOOD Corporation.  
LTR® is a registered trademark of Transcript International.  
AMBE+2™ is a trademark of Digital Voice Systems Inc.  
Windows® is a registered trademark of Microsoft Corporation.  
NXDN® is a registered trademark of JVC KENWOOD Corporation and Icom Inc.  
NEXEDGE® is a registered trademark of JVC KENWOOD Corporation.

		NX-700(H) K	NX-800(H) K
<b>RECEIVER</b>			
<b>Sensitivity</b>	<b>Digital @ 6.25 kHz (3% BER)</b>	0.20 $\mu$ V	0.28 $\mu$ V
	<b>Digital @ 12.5 kHz (3% BER)</b>		
	<b>Analog (12 dB SINAD)</b>	0.25 $\mu$ V	
<b>Selectivity</b>	<b>Analog @ 25 kHz</b>	80 dB	
	<b>Analog @ 12.5 kHz</b>	70 dB	
<b>Intermodulation</b>	<b>Analog</b>	75 dB ( $\pm$ 50,100 kHz)	
<b>Spurious Response</b>	<b>Analog</b>	90 dB	85 dB
<b>Audio Distortion</b>		Less than 3%	
<b>Audio Output</b>		4 W / 4 $\Omega$	
<b>TRANSMITTER</b>			
<b>RF Power Output</b>		30 W to 1 W	30 W to 1 W
<b>Spurious Response</b>		73 dB	75 dB
<b>FM Hum &amp; Noise</b>	<b>Analog @ 25 kHz</b>	50 dB	
	<b>Analog @ 12.5 kHz</b>	45 dB	
<b>Audio Distortion</b>		Less than 3%	
<b>Modulation</b>		16K0F3E, 14K4F1D, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

footnotes from Front:

<sup>1</sup> Requires NX subscriber unit PC Serial Interface compatible software application (e.g. Kenwood AVL & Dispatch Messaging software) or hardware (e.g. console).

<sup>2</sup> These trunked features are primarily system programming and operational dependent. Priority Monitor also requires NX subscriber settings.

## Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
<b>Low Pressure</b>	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
<b>High Temperature</b>	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
<b>Low Temperature</b>	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
<b>Temperature Shock</b>	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, III	503.5/Procedure I
<b>Solar Radiation</b>	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
<b>Rain</b>	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
<b>Humidity</b>	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
<b>Salt Fog</b>	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
<b>Dust</b>	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
<b>Vibration</b>	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
<b>Shock</b>	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
<b>International Protection Standard</b>					
<b>Dust &amp; Water Protection</b>	IP54: Radio itself IP54/55: Remote head with KRK-10				

# KENWOOD

Kenwood Electronics Canada Inc.  
Canadian Headquarters and Distribution  
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8  
www.kenwood.ca

  
www.kenwood.ca

   
JQA-1205 091  
ISO9001 Registered  
Communications Equipment Division  
Professional Systems Business Group  
JVC KENWOOD Corporation

ADS#05412 Printed in CANADA